

**DEPARTMENT OF PLANNING & ECONOMIC DEVELOPMENT  
ENGINEERING DEVELOPMENT SERVICES**

**EXHIBIT "A"  
10/17/2022**

**Mercedes-Benz of Santa Rosa Vehicle Storage Facility  
0 Coors Court  
CUP22-012**

- I. Developer's engineer shall obtain the current City Design and Construction Standards and the Engineering Development Services Department's Standard Conditions of Approval dated August 27, 2008 and comply with all requirements therein unless specifically waived or altered by written variance by the City Engineer.
- II. Per City Code Section 18-12.015 (C), all properties including commercial and industrial parcels shall be subject to public improvement requirements when the value of any proposed building or site improvement exceeds \$200,000.00. A formal review of the valuation will commence during review of the building permit application. If the valuation is determined to be above the \$200,000 threshold, the project may be required to install or modify public improvements such as sidewalks, curb and gutter, pedestrian ramps, driveway approaches, planter strips and bike lanes. Additional right-of-way and easement dedications may also be required to support the current or future expansion of the roadway in order to meet adopted City Standards, General Plan requirements or area specific plans. Contact the Engineering Division of the Planning and Economic Development Department at 707-543-3200 to discuss specific requirements.
- III. In addition, the following summary constitutes the recommended conditions of approval on the subject application/development based on the plans/reports received October 11, 2022:

**EASEMENT DEDICATIONS**

1. The Applicant shall dedicate the following Right-of-Way (ROW) along the entire project frontage for the following streets:
  - a. **Wiljan Court** – 3-feet ROW dedication for a half street ROW width of 26-feet.
  - b. **Talmadge Drive** – 26-feet ROW dedication for a half street ROW width of 26-feet
  - c. **Coors Court** – 26-feet ROW dedication for a half street ROW width of 26-feet
  - d. 35-feet radial dedications at the project frontage corners of Wiljan Court and Talmadge Drive and Coors Court and Talmadge Drive.
2. The Applicant shall dedicate a 7-feet Public Utility Easement (PUE) behind the

ROW line along the project frontage on Wiljan Court.

3. All dedication costs shall be borne by the Applicant or property owner, including preparation of any legal descriptions, plats, title reports, and deeds that are necessary. Legal descriptions and plats ("R" sheets) shall be prepared by a registered Land Surveyor or Civil Engineer licensed to practice Land Surveying in the State of California and approved by the City Engineer. City forms are available at the City of Santa Rosa Planning and Economic Development Department, Engineering Development Services Division, Room 5, City Hall.

## **PUBLIC STREET IMPROVEMENTS**

4. An Encroachment Permit is required prior to issuance of the building permit. Any improvements proposed or required, within the public right shall be reviewed and approved with the Encroachment Permit application. Only Construction plans submitted with the Encroachment Permit Application are final plans and shall be approved for construction. Contact Engineering Development Services at 543-3200, located at 100 Santa Rosa Avenue, Room 5, as soon as possible to begin Encroachment Permit application processing. Encroachment Permit application processing may take 4-6 weeks. Submit plans prepared by a licensed civil engineer showing all work in the public right of way, or in public easements, including all work on public utilities (water meter boxes, sewer lateral cleanouts, backflow devices, etc.)
5. **Wiljan Court** shall be dedicated and improved as Modified Industrial Street designations along the entire property frontage per City Standard 200H and 230G. Half width street improvements shall consist of one modified 12-foot wide travel lane, one 8-foot wide parking lane, 6-inch high concrete curb and gutter, and a 5-foot minimum width contiguous sidewalk for a half ROW width of 26-feet along with a 7-foot PUE behind the ROW line. The curb shall remain in its current location and all improvements shall be behind the existing curb line besides at the pedestrian ramp improvements at the project frontage corner of Wiljan Court and Talmadge Drive.
6. **Talmadge Drive and Coors Court** shall be dedicated and improved as Modified Industrial Street designations along the entire property frontage per City Standard 200H and 230G. Half width street improvements shall consist of one modified 12-foot wide travel lane, one 8-foot wide parking lane, 6-inch high concrete curb and gutter, and a 5-foot minimum width contiguous sidewalk for a half ROW width of 26-feet. The curb shall remain in its current location and all improvements shall be behind the existing curb line besides at the pedestrian ramp improvements at the project frontage corner of Coors Court and Talmadge Drive.
7. The improvements at the project frontage corners of Coors Court and Talmadge Drive and Wiljan Court and Talmadge Drive shall consist of ADA compliant

pedestrian ramps per Caltrans standard A88A within the limits of the ROW. Dedicate additional ROW if required. Install the new curb return to city standards.

8. Private structures such as permanent fences and BMPs etc., shall not encroach into public utility easements unless approved under a variance by the City Engineer.

## **TRAFFIC**

9. Appropriate street name signs, pavement markings, and regulatory signs, as approved by the City Engineer, shall be installed. Applicant shall be responsible for any transitional improvements required between new construction and existing improvements.
10. As applicable, City Standard 611 cobra style streetlights shall be installed along Coors Court using LEOTEK LED fixtures. Streetlight spacing, wattages, and locations shall be determined during the improvement plan review process.
11. Electrical boxes for streetlights and signals shall be provided with grounded vandal resistant inserts, McCain Tamper Resistant Inserts or City approved equal, in streetlight pull boxes at locations as directed by the City. Catalog cuts shall be provided with the first plan check submittal for review and approval by the City Engineer. The streetlight improvement plans shall include the following note; "The contractor may use their own locks during construction for ease of access, however once the conductors in the pull box are live the contractor shall coordinate with the City Inspector to have the City lock installed. Electrical pull boxes in planter strips shall be provided with a 2-foot concrete apron around box."
12. New services (electrical, telephone, cable or conduit) to new structures shall be installed underground. As applicable, the applicant shall underground overhead utilities along the project frontage and if any conflict with proposed structures per City code at their sole expense.
13. Provide sufficient line of sight so a vehicle exiting the project shall not impede or cause the oncoming traffic on Wiljan Court to radically alter their speed, based on Table 201.1 of the Caltrans' Highway Design Manual. Tree canopies shall be maintained at least 7-feet off the ground and landscaping shall be maintained at maximum 36" height within the stopping site. Install "No parking" signs and paint the curbs red within the site distance areas.
14. Avoid installation of any physical features (signs, landscaping, mailboxes, etc.) along the Wiljan Court frontage of the parcel within the traffic site distance triangles. Landscaping shall be maintained to be no more than 36" in height for low vegetation and tree canopies shall be maintained at 7-feet minimum height along the site triangle by the owner.

15. Comply with current standards for parking lot and accessible stall dimensions and signage. Submit an on-site sign and striping plan for the new parking lot improvements at first review. Submit parking lot and street lighting plans for review and approval. Lighting shall meet minimum lighting requirements.
16. The project Applicant shall be responsible for repairing/removing any debris, damage, or deterioration occurring to existing local streets and/or private driveways as a direct result of construction activity related to installation of the improvements (grading, street construction, utility installation, etc.). Required repair shall involve patching, cleaning, sealing, or overlaying affected areas as appropriate to return Wiljan Court, Talmadge Drive, and Coors Court to as good as condition as it was in prior to construction. If the project Applicant does not act prudently in a timely manner, the City shall, at its discretion, perform the correction and charge the owner/subdivider for all costs and overhead incurred.

#### **PRIVATE DRIVEWAY IMPROVEMENTS**

17. A 2-way commercial driveway apron shall be constructed in accordance with City Standard detail 250A or 250C on Wiljan Court. The private driveways shall have a minimum width of 24-feet at the back of sidewalk, unless otherwise approved by variance by the City Engineer, accessing through an additional 6-feet in width at the curb cut. Provide for a public sidewalk, level portion of sidewalk behind the driveway ramp. Paint onsite curbs red to indicate no parking along the entry ways. The driveway shall be built to City Minor street structural standards and bordered with a 6-inch concrete curb at the edge of asphalt at least 10-feet behind the driveway aprons as applicable.
18. Onsite lighting of the private parking lot shall meet minimum city standards requirements for safety and acceptable luminary standards.
19. A soils and geologic report shall be provided with the building plans submitted for review. The report shall address the new pavement sections within the parking lot for adequacy to City codes.
20. Maximum grade difference at project boundary to offsite property shall be less than 1 foot vertically, unless reviewed and approved by the City Engineer.
21. Any offsite drainage entering the site shall be either conveyed through the site, via a private drainage system with accompanying easements dedicated to the upstream property owners or accepted into the private drainage and LID system for the project. The final LID design shall address the acceptance of any offsite flows.
22. Submitted grading and drainage plans shall show typical and specific cross-sections at all exterior property lines and interior lot lines indicating the adjacent elevations at the join grades to adjacent parcels including graded slopes, swales,

fences, retaining walls and sound walls as applicable.

## **PUBLIC STORM DRAINAGE**

23. Other agency permits, as required to complete the project, shall be obtained by the Applicant at the Applicant's sole expense.
24. Public storm drainage shall be designed to City of Santa Rosa Design and Construction Standards and Sonoma County Water Agency (SCWA) current 2020 flood management design manual standards by a licensed Civil Engineer. All storm water run-off shall be collected via an underground drainage system and discharged to the nearest public downstream facility possessing adequate capacity to accept the run-off. Preliminary and final storm drain hydrology and hydraulic design reports as approved by the Sonoma County Water Agency or a designated agent shall be provided to the City of Santa Rosa for the city file prior to encroachment permit issuance. Provide engineering calculations of adequacy for the downstream storm drain connections for project flow volumes. Upsize any storm drainage facilities that do not have adequate capacity to the approval of the City Engineer.
25. Drainage patterns shall follow the Regional Master Drainage Plan as depicted in the current master drainage studies available for the local area as provided by Sonoma County Water Agency (SCWA). Changes/diversions to the contributory drainage areas for regional water sheds are not permitted without City Engineer review and approval.
26. As applicable, all drainage flows from offsite shall be intercepted at the property line and conveyed through a private system to discharge into the public right of way. Onsite storm drain design shall be reviewed and approved by the City Building Official. Regional Public storm drain design shall be reviewed and approved by SCWA for compliance with County and City design standards.
27. All onsite storm drain inlets shall be labeled per the City standard detail 409 - "DRAINS TO CREEK" or an approved equal.
28. Contractor shall not use the sanitary sewer system or storm drainage system to release construction water from the site unless they have a valid discharge permit to do so. Application for Industrial construction water discharge permit can be obtained from the City of Santa Rosa Environmental Compliance Department. Contact Renae Gundy at 707-543-4368.
29. Any existing storm drain stub outs to the property that shall not be used shall be abandoned at the main per City Design Standards.
30. Drainage from landscape areas are not allowed to cross over curb or sidewalk and are to outlet to a street or drainage channel through City Standard curb

drains or other acceptable means.

31. Lot drainage and private storm drain facilities shall be approved by the Chief Building Official's designated representative. All private drainage facilities shall be privately owned and maintained.
32. All offsite storm drain work and coordination with any adjacent neighbors to the project, and all off site construction and or access easements as needed to construct the project shall be obtained at the sole cost of the applicant prior to entitlement.
33. If flows exceed street capacity, flows shall be collected via an underground drainage system (with minimum 15" diameter and maximum 72" diameter pipe sizes) and discharged to the nearest approved downstream facility possessing adequate capacity to accept the runoff, per the City's design requirements. Such runoff systems shall be placed within public street right-of-way wherever possible.
34. Private drainage systems are to be connected to a public system from a private field inlet located behind the sidewalk and or through a minimum 15-inch RCP or HDPE storm drainpipe through the public right-of-way, public utility easement or storm drain easement to a public drainage structure. No blind connections are permitted into public storm drain system. Public storm drains shall be shown on the plans in a design profile. Install a city standard storm drain structure at any change of pipe size, pipe grade or pipe direction.
35. For purposes of leak detection and maintenance access, no reinforced concrete shall be designed over publicly maintained storm water drainpipe facilities. Unreinforced concrete shall be allowed under special circumstances such as crosswalks. Storm drain inlets shall be located outside of the concrete area. Storm drainage facilities in the private road and private driveway shall be maintained by the lot owner.

#### **STORM WATER COMPLIANCE (SWLID)**

36. The Applicant's engineer shall comply with all requirements of the latest edition of the City Standard Urban Storm Water Low Impact Development Plan (SWLID) Guidelines. Final onsite Improvement Plans shall incorporate all SWLID Best Management Practices (BMP's) and shall be accompanied by a Final Onsite Storm Water Mitigation Plan which shall address the storm water quality and quantity. Final Improvement Plans shall be accompanied by a maintenance agreement or comparable document to assure continuous maintenance in perpetuity of the SWLID BMP's and shall include a maintenance schedule.
37. Perpetual maintenance of SWLID Best Management Practices (BMP's) shall be the responsibility of the lot owner. The Lot owners shall be responsible for

performing and documenting an annual inspection of the BMP's on their respective properties. The annual reports shall be retained by the Lot owner for a period of the latest five years and shall be made available to the City upon request.

38. After the SWLID BMP improvements have been constructed, the Applicant's Civil Engineer or qualified professional is to prepare and sign a written certification that they were constructed and installed as required. Written certification of SWLID BMP's is to be received by the City prior to issuance of occupancy. Written certification of SWLID required improvements is to be received by the City prior to occupancy. The maintenance schedule and the Final SUSMP are to be included as part of the owners' records. All BMP's shall be maintained, replaced, and repaired by the lot owner unless an agreement is accepted in writing by the City Engineer.
39. The SWLID "Declaration of Maintenance" document shall be recorded prior to Building permit issuance.
40. BMP's and private drainage facilities shall be located outside of Public Utility easements and/or utility easements.
41. The Civil Engineering plans shall show sufficient construction details and dimensions of each BMP device on the drawings, so the BMP may be replaced in the future. Landscape plans and civil plans shall be coordinated with the approved SUSMP report and show the BMP locations clearly to prevent them from being filled in with landscape materials. The landscape and civil plans shall be updated to reflect the final BMP locations, shapes, sizes and construction dimensions to install the BMP features per the final construction.
42. No debris, soil, silt, sand, bark, slash, sawdust, rubbish, cement or concrete washings, oil or petroleum products, or other organic or earthen material from any construction or associated activity of whatever nature, shall be allowed to enter into or be placed where it may be washed by rainfall into the storm drain system. When operations are completed, any excess material or debris shall be removed from the work area.
43. As applicable, where bio-retention basins are installed, then transformers, meter boxes, cleanouts, fire hydrants, etc. shall be located without conflict with the basins. Locations of infrastructure shall be reviewed during plan check. Each trench crossing shall extend the length of a BMP basin by 5 additional linear feet. Locations of infrastructure should be present on the plans and shall be reviewed during plan check.
44. All offsite work resulting in new impervious area (sidewalk, driveways, pedestrian ramps, etc.) shall be treated by LID BMPs sized for all tributary flows. Treatment offsets may be considered and shall be approved by the Stormwater department

and if required the Regional Water Board prior to building permit issuance.

## **WATER AND WASTEWATER**

45. All irrigation services shall be protected with a reduced pressure backflow device per City Standard 876. Backflow additions or upgrades shall be required as part of the building permit review. The location of all existing or proposed backflow devices shall be shown on the utility plan submitted with the building permit application.
46. If additions or modifications to the existing landscaping are proposed under the building permit application, a dedicated irrigation meter shall be installed to serve the existing or proposed landscaping if one does not already exist.
47. Any water or sewer services that will not be used shall be abandoned at the main.
48. Any additions or modifications to the existing landscaping shall be consistent with the Water Efficient Landscape Ordinance adopted by the Santa Rosa City Council, Ordinance 4051, on December 1, 2015. Landscape plans will be reviewed during the building permit stage to determine compliance with the ordinance.

## **ENVIRONMENTAL COMPLIANCE**

49. Tenant improvements performed in conjunction with a change of use or an expansion of an existing use may result in additional requirements associated with the discharge to the City's public wastewater system. Contact the Water Department's Environmental Compliance section at 707-543-3369 to determine the necessary permitting path and to better understand the specific requirements that will be brought forward during the review of the building permit application.

## **RECREATION & PARKS – (from Tim Bernard dated July 28, 2022)**

50. Should the conditional use of this property extend beyond the proposed three years, street trees will be required and planted by the owner/developer. This condition appears to have been met by the addition of street trees with the most recent plan submittal.
51. Selection of street trees will be made from the City's approved master plan list and inspected by the Parks Division may occur. Planting shall be done in accordance with the City *Standards and Specifications for Planting Parkway Trees*. Copies of the master street tree list and the standards are available at the Parks Division Office (707) 543-3770. This declaration shall be added to the General Notes of the improvement plans.
52. All landscaping, which includes bioretention areas, street trees and associated landscaping, shall be privately maintained and irrigated, including in Right of Ways. Property owners shall be responsible for the irrigation and maintenance of



the street trees and maintenance of the planter strips in front of and alongside of their lots, including any bioretention area in these spaces.



10/17/2022

---

CLEVE GURNEY, PE - EDS ASSOCIATE ENGINEER