

Santa Rosa Memorial Medical Office Building and Parking Structure Project

Mitigation Monitoring and Reporting Program

Lead Agency:

City of Santa Rosa Community Development Department 100 Santa Rosa Avenue, Rm. 3 Santa Rosa, CA 95404

Contact: Patrick Streeter, Senior Planner

Prepared By:

Jean Kapolchok & Associates 843 2nd Street Santa Rosa, CA 95404

December 10, 2017

MITIGATION MONITORING AND REPORTING PROGRAM

INTRODUCTION

The California Environmental Quality Act (CEQA) requires that when a public agency has made findings that mitigation measures are required to avoid or substantially lessen significant adverse environmental impacts identified in a Mitigated Negative Declaration (MND), the agency shall adopt a program for monitoring or reporting on the mitigation to ensure the mitigation measures are implemented. This Mitigation Monitoring and Reporting Program (MMRP) has been prepared to ensure the effective implementation of the mitigation measures that the City of Santa Rosa Planning Commission and Design Review Board adopted as part of their approval of the Santa Rosa Memorial Medical Office Building and Parking Structure Project, as set forth in the Mitigated Negative Declaration for the project.

The city of Santa Rosa Planning and Economic Development Department, with assistance from J. Kapolchok & Associates, prepared the Mitigated Negative Declaration. The city of Santa Rosa, as the designated lead agency for the project, is responsible for enforcing and verifying that each mitigation measure is implemented.

The MMRP establishes the framework the city of Santa Rosa, and others will use to implement the mitigation measures adopted in connection with project approval, and the monitoring/reporting of such implementation. "Monitoring" is generally an ongoing or periodic process of project oversight. "Reporting" generally consists of a written compliance review.

This MMRP provides a framework to document implementation of the required mitigation and identifies monitoring/reporting responsibility.

The attached MMRP table identifies the mitigation measures, monitoring/mitigation timing, responsible person/ agency, monitoring procedures, and a record of implementation of the mitigation measures. The numbering of mitigation measures follows the numbering sequence found in MND/Initial Study.

Mitigation Measure	Compliance	Timing	Responsible	Status	Date of
Willigation Weasure	Documentation	Tilling	Party	Status	Completion
		O1:4	rarty		Completion
MM AO 1. D. start E. t. st		Quality	Davis		
MM-AQ-1: Dust and Exhaust Controls The contractor shall implement the following best management practices that are required of all projects: 1. All exposed surfaces (e.g., parking areas, staging areas, soil piles, graded areas, and unpaved access- roads shall be watered two times per day. 2. All haul trucks transporting soil, sand, or other loose material off-site shall be covered. 3. All visible mud or dirt track- out onto adjacent public roads shall be removed using wet power vacuum street sweepers at least once per day. The use of dry power sweeping is prohibited. 4. All vehicle speeds on unpaved roads shall be limited to 15 miles per hour (mph). 5. All roadways, driveways, and sidewalks to be paved shall be completed as soon as possible. Building pads shall be laid as soon as possible after grading unless seeding or soil binders are used. 6. Idling times shall be minimized either by shutting equipment off when not in use or reducing the maximum idling time to 5 minutes (as required by the California airborne toxics control measure Title 13, Section 2485 of California Code of Regulations [CCR]). Clear signage shall be provided for construction workers at all access points. 7. All construction equipment shall be maintained and properly tuned in accordance with manufacturer's specifications. All equipment shall be checked by a certified mechanic and determined to be running in proper condition prior to operation. 8. Post a publicly visible sign with the telephone number and	Documentation that the requirements have been incorporated into the construction contracts. Documentation of compliance to be provided during construction.	During any construction period ground disturbance.	Project applicant or their designee for submittal of required information. Department of Planning and Economic Development prior to permit issuance. Building Division during site review.		

person to contact at the Lead Agency regarding dust complaints. This person shall respond and take corrective action within 48 hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
regarding dust complaints. This person shall respond and take corrective action within 48 hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
person shall respond and take corrective action within 48 hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
corrective action within 48 hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
The Air District's phone number shall also be visible to ensure compliance with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
District's phone number shall also be visible to ensure compliance with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
be visible to ensure compliance with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
with applicable regulations. MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
MM-AQ-2: Equipment Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
Emissions Control Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
Selection of equipment during construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
construction to minimize emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
emissions. Such equipment selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
selection would include the following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
following: 1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
1. All diesel-powered off-road equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
equipment larger than 25 horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
horsepower and operating on the site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
site for more than two days continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
continuously shall, at a minimum, meet U.S. EPA particulate matter emissions standards for Tier 2
meet U.S. EPA particulate matter emissions standards for Tier 2
emissions standards for Tier 2
engines.
Note that the construction
contractor could use other
measures to minimize
construction period DPM
emissions to reduce the predicted cancer risk below the thresholds.
Such measures may be the use of
alternative powered equipment (e.g., LPG-powered lifts),
alternative fuels (e.g., biofuels),
added exhaust devices, or a
combination of measures,
provided that these measures are
approved by the City and
demonstrated to reduce
community risk impacts to less
than significant.
Biological Resources
MM-BR-1: Pre-construction a. Site construction b. Outside of Project
Nesting Bird Survey activities, such as March 1 applicant or
1. For tree removal occurring watering, disking, through their designee
during the breeding season vegetation clearing, August 31. for submittal
togonioni poding souson programon clearing, program of the first of the submitted program of the first of the submitted program of the submitted p
(March 1 through August 31), a demolition, and grading of required
(March 1 through August 31), a demolition, and grading of required
(March 1 through August 31), a demolition, and grading qualified biologist shall conduct shall be conducted of required information.



2. If active bird nests are found	not feasible for such		Economic	1	
during preconstruction surveys:	activities to occur		Development		
a. A 500-foot no-disturbance	outside of these time		prior to permit		
buffer will be created around	periods, then the project		issuance.		
active raptor nests during the	shall comply with the		issualice.		
breeding season or until it is	requirements outlined in				
determined that all young have	b. through d., below.				
fledged, and	b. tillough d., below.				
b. A 250-foot buffer zone will be	b. If construction	c. Prior to			
created around the nests of other	activities, such as	c. Prior to initiation of			
special status birds and all other	watering, disking,	construction			
birds that are protected by	vegetation clearing,	activities.			
California Fish and Game Code	demolition, and grading	activities.			
3503.	occur between March 1				
c. These buffer zones are	and August 31, then a				
consistent with CDFW avoidance	qualified biologist shall				
guidelines and CDFW buffers	conduct a pre-				
required on other similar projects;	construction survey of				
however, they may be modified in	all potential nesting				
coordination with CDFW based	habitats.				
on existing conditions at the	inoims.				
project site.	c. If nesting surveys are	d. Within one			
3. If pre-construction surveys	conducted, the results of	week of			
indicate that nests are inactive or	the survey(s) shall be	completion			
potential habitat is unoccupied	summarized in a letter	of nesting			
during the tree removal period, no	report made available to	birds			
further mitigation is required.	the Department of	survey(s).			
Shrubs and trees that have	Planning and Economic	, ,			
been determined to be unoccupied	Development within				
by special status birds may be	one week of the				
removed.	completion of the				
4. If vegetation removal activities	survey.				
are delayed or suspended for					
more than two weeks after the	d. If active nests are	e. At qualified			
preconstruction survey, the area	located pursuant to b.	biologist's			
shall be resurveyed.	mitigations measured	discretion.			
	outlined in MM-BR-1				
MM-BR-2: <u>Tree Preservation</u>	shall be implemented.				
1. All removed trees shall be			_		
mitigated in accordance with the	a. A final summary of all	a. After final	Project		
city of Santa Rosa Tree	trees subject to the city	Design	applicant or		
Preservation Ordinance, which	of Santa Rosa Tree	Review and	their designee		
requires the planting of two (2)	Ordinance and a	prior to	for submittal		
15-gallon trees on site, on public	mitigation plan (tree	permit	of required		
property, an in-lieu payment of	replacement and/or in-	issuance for	information.		
\$100.00 per tree or a combination	lieu payment) shall be	tree	Donortmant of		
of options.	prepared.	removal.	Department of		
			Planning and Economic		
			Development		
			prior to permit		
			issuance.		
	Geology	and Soils			
MM-GEO-1: Building Codes	Documentation that the	Prior to building	Project		
	requirements have been	permit issuance.	applicant or		
-		•			

All structures shall be designed in accordance with California Building Code (CBC) and any local amendments thereto in place at the time of building permit submittal. MM-GEO-2: Geological Investigation All recommendation of the preliminary geologic	incorporated into the building construction plans. A qualified geologist or geological engineer shall prepare a geological report in accordance with all	Prior to building permit issuance.	their designee for submittal of required information. Department of Planning and Economic Development and the Building	
investigation prepared for the project prior to the issuance of building and grading permits shall be incorporated into the project design. MM-GEO-3: Site Drainage The Project Civil Engineer shall design the site drainage to collect surface water into storm drain	applicable federal, state and local requirements. Documentation that the requirements have been incorporated into the construction documents. A qualified civil engineer shall propers a final site.	Prior to issuance	Division prior to permit issuance.	
surface water into storm drain systems and discharge water at appropriate locations. Erosion control measures during and after construction shall conform to the most recent version of Erosion and Sediment Control Field Manual prepared by the North Coast Regional Water Quality Control Board.	shall prepare a final site drainage plan in accordance all applicable federal, state and local requirements. Documentation that the requirements have been incorporated into the final grading and drainage plan.	of any grading permit.		
	N	loise		
MM-NOISE -1: Vibration Foundation support piles within 60 feet of the adjacent office buildings or within 95 feet of the adjacent apartment building should either be installed using vibratory drivers or drilled and cast in place piers.	Documentation that the requirements have been incorporated into the construction contracts. Documentation of compliance to be provided during construction.	Prior to and during construction.	Project applicant or their designee for submittal of required information. Department of Planning and Economic Development prior to permit issuance. Building Division during site review.	
		ation/Traffic		
MM-TRANS/TRAFFIC- 1: Traffic Signal	A traffic signal shall be installed at the intersection of Sonoma Avenue and Sotoyome	Prior to issuance of a final occupancy permit.	Project applicant or their designee for submittal	

			,	
A traffic signal is warranted at the	Street in accordance with		of required	
intersection of Sonoma Avenue/	criteria and design set forth		information.	
Sotoyome Street. Said signal shall	by the city of Santa Rosa			
be installed in accordance with	Transportation and Public		Department of	
criteria and design set forth by the	Works Division.		Transportation	
city of Santa Rosa Transportation			and Public	
and Public Works Division.			Works prior to	
			final	
MM-TRANS/TRAFFIC- 2:	A RRFBs shall be installed		occupancy	
RRFBs	at the new crossing location		permit.	
A Rapid Rectangular Flashing	on Montgomery Drive		r · · · · · ·	
Beacons (RRFBs) shall be	between Sotoyome Street			
installed at the new crossing	and Doyle Park Drive in			
location on Montgomery Drive	accordance with criteria and			
between Sotoyome Street and	design set forth by the city			
Doyle Park Drive.	of Santa Rosa			
Boyle I aik Bilve.	Transportation and Public			
MM-TRANS/TRAFFIC- 3:	Works Division.			
Sight Distance	Works Division.			
Landscaping should be	All recommendations shall	Prior to final	Project	
maintained such that foliage stays	be incorporated into the	Design Review.	landscape	
above seven feet and below three	project landscape plan.	Design Review.	architect.	
feet from the ground within the	project landscape plan.		arcintect.	
sight lines at the driveways. Signs			City of Santa	
or monuments to be installed			Rosa Design	
along the project frontage should			Review Board	
be placed so that sight distance is			and the	
not obstructed at the project			Department of	
driveways. Further, red paint			Planning and	
should be applied to the curbs for			Economic	
35 feet on either side of the			Development.	
project driveway on Sotoyome			Development.	
Street to improve sight lines.				
Succe to improve sight lines.				

